

performance road – tight handling – fast acceleration
 comfortable – balanced – durable – fun – handcrafted value



UPDATED



VAMOOTS CR

FRAME SPECIFICATIONS

- HEAD TUBE 44mm
- BOTTOM BRACKET 68mm threaded
- SEATPOST 27.2
- FRONT DERAILLEUR CLAMP 34.9
- MAX TIRE CLEARANCE 28mm
- FRAME WEIGHT 1375 grams (55cm)

Hardworking, compact-geometry road bike for everything from elite-level racing to performance recreational riding

Moots Pi-Tech 3/2.5 CWSR seamless tube set, oversized and size-specific tubing for unbeatable ride quality

Oversized chain stays and hooded dropouts for increased power transfer to rear wheel

44mm head tube now standard on the Vamoots CR

Nine stock sizes using variable geometry and size-specific tubing for the optimal fit and ride

By combining the best materials with the best craftsmanship we deliver long-term performance with our lifetime warranty

Dedicated ride-tuned Moots monocoque tapered carbon fork available in two rakes – matte black finish only

SUGGESTED BUILD KIT

- FORK Moots 1.25 Tapered Carbon (Black)
- STEM Fizik Cyrano
- SEATPOST Fizik Cyrano
- GROUP Shimano Ultegra 6870
- WHEELSET Shimano Ultegra
- TIRES Schwalbe Durano
- HEADSET/BB Chris King I8/Ultegra BB
- HANDLEBAR Fizik Cyrano R3
- SADDLE Fizik Aliante R3

HOW WE STACK UP

- The best choice for performance and lifetime durability, compare to any bike at the same price
- Handcrafted excellence with timeless looks and durable finish; not just paint and flash
- Nine stock sizes to fit most; full custom available with many options
- Maximized use of U.S.-made materials to maintain the highest-quality ride, durability, and workmanship
- Designed and constructed in Colorado by cyclists for cyclists with one goal: build the best bike

GEOMETRY TABLE

| FRAME SIZE [CM] | EFFECTIVE TOP TUBE [CM] | SEAT TUBE /C- T/ [CM] | HEAD TUBE LENGTH [CM] | HEAD ANGLE | SEAT ANGLE | BB DROP [CM] | CHAIN STAY LENGTH [CM] | STAND-OVER [IN] | TOP TUBE SLOPE | FORK RAKE [MM] | STACK | REACH |
|-----------------|-------------------------|-----------------------|-----------------------|------------|------------|--------------|------------------------|-----------------|----------------|----------------|-------|-------|
| 48 | 51.5 | 45.0 | 11.0 | 72.50 | 74.75 | 7.4 | 40.5 | 28.4 | 12.2 | 50 | 535 | 369 |
| 50 | 52.5 | 47.0 | 11.5 | 72.75 | 74.50 | 7.4 | 40.5 | 28.9 | 10.3 | 50 | 541 | 375 |
| 52 | 53.5 | 48.5 | 12.5 | 73.00 | 74.25 | 7.3 | 40.5 | 29.4 | 9.7 | 50 | 552 | 380 |
| 54 | 54.5 | 50.0 | 14.0 | 73.25 | 74.00 | 7.2 | 40.5 | 30.0 | 9.5 | 50 | 566 | 383 |
| 55 | 55.5 | 51.0 | 15.0 | 73.50 | 73.50 | 7.2 | 40.7 | 30.3 | 9.6 | 43 | 576 | 385 |
| 56 | 56.5 | 52.0 | 16.0 | 73.50 | 73.25 | 7.2 | 40.7 | 30.7 | 9.4 | 43 | 586 | 390 |
| 58 | 57.5 | 53.5 | 17.5 | 73.75 | 73.00 | 7.1 | 41.0 | 31.3 | 9.3 | 43 | 601 | 392 |
| 60 | 58.5 | 55.0 | 19.0 | 74.00 | 73.00 | 7.0 | 41.0 | 31.9 | 9.2 | 43 | 616 | 398 |
| 62 | 59.5 | 57.0 | 21.0 | 74.25 | 72.50 | 6.8 | 41.5 | 32.7 | 9.0 | 43 | 634 | 397 |

STANDOVER MEASURED WITH 23C TIRE / MAX TIRE WIDTH 28MM / STACK AND REACH MEASURED WITH CX I8I7 EXTERNAL LOWER CUP AND INSET TOP HEADSET

OPTIONS TO CONSIDER

- 1cm longer head tube
- Internal electronic wire routing for both Shimano and Campy
- Full custom sizing; partnering with our dealers, we will create the perfect ride
- Pump peg, chain hanger, third water bottle, SGS couplers
- Engraved & etched option