

DECAL REPLACEMENT INSTRUCTIONS



MOOTS
HANDBUILT IN THE ROCKIES

2545 COPPER RIDGE DRIVE
STEAMBOAT SPRINGS, CO 80487
970.879.1676

MOOTS.COM

PLEASE READ THROUGH ENTIRE INSTRUCTIONS BEFORE STARTING!!!

To get the best possible application of your new decal set, please read and carefully follow these steps:

REMOVE OLD DECALS:

- (1)** Start by washing entire bike. Use hot soapy water, or a Simple Green mix to remove dirt, grease, etc. from frame. (Your Moots will love you for this alone)
- (2)** Remove old decal set: If your bike has decals from 2004 or earlier, you must use Acetone to remove them. You can find this at any hardware store. Use a clean (lint-free) paper towel or cloth to remove decals. The decal will leave a milky residue if you don't change out the towel or cloth.
- (3)** If your bike has decals from 2005 or later, you must use a heat gun or hairdryer. Heat the decals, then peel. **USE EXTREME CAUTION! THE DECALS GET VERY HOT, AND YOU COULD BURN YOURSELF VERY SEVERELY!**
- (4)** After removal of the decal set, make one last check to make sure you have removed all residues.

APPLY NEW DECALS: In order for the decals to adhere to the frame, make sure the bike has been in a warm room before attempting to apply the decals.

- (1)** Place the decal onto the chosen area of the frame, making sure it is straight and even. (This takes a good eye)...do your best.
- (2)** As you lay the decal down on the frame use your hand to help it along. Go slowly and evenly to make sure you do not leave any bubbles or wrinkles. After repeating this process to cover all the decals on the frame, use a soft plastic card (drivers license or something similar) to firmly press the decal onto the frame.
- (3)** Let the decals "set" on the frame overnight so the glue can bond to the frame, then peel off the clear coating. Go slow, making sure not to tear or peel up the decal.
- (4)** Once complete with the application use Lemon Pledge on the frame to shine the frame to its original luster.